

Dolly 64 - 210

The Dolly 64 - 210 will speed up processes within your supply chain with quick cross-stacking, increasing handling efficiency and an innovative uni-link feature, enabling short side and long side linking.

Key Benefits



Uni-link Dolly

The Uni-link feature is what makes the Loadhog Dolly so versatile. Link units on either the short side or the long side to move multiple loads or prepare for transport.



Quick cross-stack

The Dolly 64 - 210 can be securely cross stacked which is quicker to achieve and a reduced stacking pitch of 56 mm, 59.5 mm smaller than if the Dolly was straight stacked.



ALC & Pallet Lid compatible

This Dolly is compatible with all Loadhog Attached Lid Containers and can be linked on the long side and then secured with a Half-Euro Pallet Lid.



4 x Non-marking swivel castors

As standard this Dolly is fitted with four swivel castors and Ø75 mm non-marking TPR wheels, preserving your supply chain aesthetics.



Secure banding

The central sub-flush banding regions on all sides of the Dolly ensure that any banding remains in place, safely securing the load throughout its journey.



Eco-Friendly

The Dolly-64-210 is made from recycled plastic making it eco-Friendly as well as cost effective.

Accessories & Options



Dolly Handle

The Dolly handle enables increased control and enhanced ergonomics, preventing the user from having to bend down.



Embossed Branding

Go that step further with a custom Dolly and have your logo moulded into the deck. (MOQs Apply)




Product configuration

We offer special product configurations to ensure the solution provided is the best possible solution for you.



Standard Colours



Other colours available (MOQ's Apply)



Digital & Embossed Printing

Digital Position:	Right on long side
Max Size Digital:	50 mm (H) x 125 mm (W)
Embossed Position:	Short side insert on deck
Max Size Embossed:	49 mm (H) x 98 mm (W)

Specification sheet

All dimensions are nominal and subject to manufacturing tolerances.

Dimensions (mm)	
Length	594
Width	396
Height	149
Stacking pitch (cross-stacked)	56
Stacking pitch (straight-stacked)	115.5
Ground clearance	85.5

Material	
Deck type	Open
Deck material	High impact polypropylene
Temp resistance	-20°C to +40°C
Castor type	4 swivel
Top plate	Zinc plated steel
Wheel material	Non-marking TPR
Wheel Diameter	ø75 mm

Pallet quantities	
Pallet type	Euro
Quantity per pallet	64
Height (m)	2.3

More packaging information can be found within the 'Official Standard Packaging Document', any deviations from this should be advised when the order is placed

Weight and performance (kg)	
Weight	2.0
Weight (deck)	1.0
Weight (castors x4)	1.0
Payload	210
Max stack quantity	19